

METHOD FOR AUTOMATIC LAYOUT OF SWITCHED NETWORK TOPOLOGIES

5

FIELD OF THE INVENTION

The present invention relates generally to networks and, more particularly, to the management of networks, and, even more particularly, to the topological layout of switched networks.

10

BACKGROUND OF THE INVENTION

As communications networks, such as the Internet, carry more and more traffic, efficient use of the bandwidth available in the network becomes more and more important. Switching technology was developed in order to reduce congestion and associated competition for the available bandwidth. Switching technology works by restricting traffic. Instead of broadcasting a given data packet to all parts of the network, switches are used to control data flow such that the data packet is sent only along those network segments necessary to deliver it to the target node. The smaller volume of traffic on any given segment results in fewer packet collisions on that segment, and thus the smoother and faster delivery of data. A choice between alternative paths is usually possible and is typically made based upon current traffic patterns.

15

20

25

The intelligent routing of data packets with resultant reduction in network congestion can only be effected if the network topology is known. The topology of a network is a description of the network which includes the location of and interconnections between nodes on the network. The word "topology" refers to either the physical or logical layout of the network, including devices, and their connections in relationship to one another. Information necessary to create the topology layout can be

derived from tables stored in network devices such as hubs, bridges, and switches. The information in these tables is in a constant state of flux as new entries are being added and old entries time out. Many times there simply is not enough information to determine where to place a particular device.

5 Switches examine each data packet which they receive, read their source addresses, and log those addresses into tables along with the switch ports on which the packets were received. If a packet is received with an unknown target address, the switch receiving it broadcasts that packet to each of its ports. When the switch receives a reply, it will have identified where the new node lies.

10 In a large network with multiple possible paths from the switch to the target node, this table can become quite large and may require a significant amount of the switch's resources to develop and maintain. As an additional complication, the physical layout of devices and their connections are typically in a state of constant change. Devices are continually being removed from, added to, and moved to new physical locations on the
15 network. To be effectively managed, the topology of a network must be accurately and efficiently ascertained, as well as maintained.

 In a switch, each port of the switch forms a so called "collision domain." Existing techniques for ascertaining the topology of a network involve creating a so called "container" or "segment" for each collision domain. Thus, the topological map of the
20 network ends up with one container or segment per port for each switch.

 Current methods for creating topological maps in networks containing switches can cause a proliferation of segments. Although such proliferation of segments may be correct under the product's layout models, it causes the network level sub-map to be cluttered and often unusable. As an example, a port on a switch connected to a node
25 would create a new segment on the topological map, as would the attachment of a port on a switch to a port on another switch. For a network comprising a large number of switches and nodes the number of segments and associated table entries can quickly become very large and unwieldy resulting in the heavy use of computer resources in creating and maintaining network topological data. Thus, there exists a need for a
30 method of creating a topological map of a network which is accurate, frugal in its

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

SUMMARY OF THE INVENTION

5 The present patent document relates to a novel method for intelligently and automatically laying out the topologies of switched networks. Previous methods for laying out the topologies of switched networks have relied upon creating a segment for each and every switch port connected to a node and upon creating a segment for each port of a switch that is connected to a port of another switch.

10 As used herein, a node is any electronic device or combination of electronic devices with their interconnections. In the representative embodiments disclosed, the nodes could be for example combinations of interconnected electronic devices, such as but not limited to other networks and sub-networks. Also, the nodes could be terminals, workstations, personal computers, printers, scanners, or any other electronic device which can be connected to networks.

15 Also as used herein, a switching device is any device that controls the flow of messages on a network. Switching devices include, but are not limited to, any of the following devices: repeaters, hubs, routers, bridges, and switches.

20 In representative embodiments, bus segments are disclosed wherein a bus segment comprises two or more nodes connected to a port of a switching device, serial segments are disclosed wherein a serial segment comprises a port on one switching device connected to a port on another switching device, and star segments are disclosed wherein a star segment comprises all ports with attached nodes on a switching device that have only one node connected to each port.

25 A primary advantage of the embodiment as described in the present patent document over prior techniques is the reduction in the number of segments created in topological maps of the network with a resultant simplification of the topology maps for networks. It is recognized that the topological mapping referred to herein may be contained in one or more tables, and it is not necessarily required for the mapping system to create the map as a drawing. The simplifications provided in the representative embodiments of the present application provide further advantage in reducing the
30 consumption of valuable system resources.

Other aspects and advantages of the present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

00990871-031600

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings provide visual representations which will be used to more fully describe the invention and can be used by those skilled in the art to better understand it and its inherent advantages. In these drawings, like reference numerals
5 identify corresponding elements and:

Figure 1 is a drawing of a typical topological bus segment for representing the connectivity of nodes on a network as described in various representative embodiments of the present patent document.

10 Figure 2 is a drawing of a typical topological serial segment for representing the connectivity of nodes on the network as described in various representative embodiments of the present patent document.

Figure 3 is a drawing of a typical topological star segment for representing the connectivity of nodes on the network as described in various representative embodiments of the present patent document.
15

Figure 4 is a drawing of another typical topological star segment for representing the connectivity of nodes on the network as described in various representative embodiments of the present patent document.

Figure 5 is a drawing of the connectivity of an example network system.

20 Figure 6 is a drawing of the connectivity of the example network system of figure 5 illustrating the location of typical segments.

Figure 7 is a drawing of a reduced segment topological map of the example network system of figure 5 as described in various representative embodiments of the present patent document.

25 Figure 8 is a flow chart of the method steps performed in creating reduced segment topological maps as described in various representative embodiments of the present patent document.

Figure 9A is a flow chart of a portion of the method steps of figure 8 performed in creating the reduced segment topological map as described in various representative
30 embodiments of the present patent document.

Figure 9B is a flow chart of a continuation of a part of the flow chart of figure 9A as described in various representative embodiments of the present patent document.

Figure 9C is a flow chart of a continuation of another part of the flow chart of figure 9A as described in various representative embodiments of the present patent document.

Figure 10 is a drawing of a computer used for creating and managing reduced segment topological maps for representing the connectivity of nodes on the network as described in various representative embodiments of the present patent document.

09526830 031600

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in the drawings for purposes of illustration, the present patent document relates to a novel method for intelligently and automatically laying out the topologies of switched networks. Previous methods for laying out the topologies of switched networks have relied upon creating a segment for each and every switch port connected to a node and upon creating a segment for each port of a switch that is connected to a port of another switch. In the following detailed description and in the several figures of the drawings, like elements are identified with like reference numerals.

1. Definitions:

As used herein, a node is any electronic device or combination of electronic devices with their interconnections.

A switching device is any device that controls the flow of messages on a network.

Switching devices include, but are not limited to, any of the following devices: repeaters, hubs, routers, bridges, and switches.

Figure 1 is a drawing of a typical topological bus segment **100** for representing the connectivity of nodes on a network **110** as described in various representative embodiments of the present patent document. In figure 1, a first and second nodes **121,122**, as well as a first port **131** of a first switching device **140** are interconnected via the network **110**. The bus segment **100** comprises the first and second nodes **121,122** connected to the first port **131** of the first switching device **140**. Nodes heard on a common port of a switch are placed into a bus segment.

Figure 2 is a drawing of a typical topological serial segment **200** for representing the connectivity of nodes on the network **110** as described in various representative embodiments of the present patent document. In figure 2, the first node **121** comprises a second port **132** on a second switching device **145** which is connected via the network **110** to the first port **131** on the first switching device **140**. The serial segment **200** comprises the second port **132** on the second switching device **145** connected to the first port **131** on the first switching device **140**.

Figure 3 is a drawing of a typical topological star segment 300 for representing the connectivity of nodes on the network 110 as described in various representative embodiments of the present patent document. In figure 3, the first node 121 is connected to the first port 131 of the first switching device 140. The star segment 300 comprises the first node 121 connected to the first port 131 of the first switching device 140.

Figure 4 is a drawing of another typical topological star segment 300 for representing the connectivity of nodes on the network 110 as described in various representative embodiments of the present patent document. In addition to the connections described with respect to figure 3, a third node 123 is connected to a third port 133 of the first switching device 140 and a fourth node 124 is connected to a fourth port 134 of the first switching device 140. In figure 4, the star segment 300 comprises the first node 121 connected to the first port 131 of the first switching device 140, the third node 123 connected to the third port 133 of the first switching device 140, and the fourth node 124 connected to the fourth port 134 of the first switching device 140. Thus, the star segment 300 comprises, on a given switching device, at least one port, wherein one and only one node is connected to that port, and that node. In the more general case, the star segment 300 comprises, on a given switching device, all ports having one and only one node connected to each port, and those connected nodes. Since the segments drawn using the topological methods of figure 4 resemble a star, they are referred to as star segments.

For illustrative purposes, nodes in the figures described above and in subsequent figures are shown as individual electronic devices or ports on switching devices. However, in other representative embodiments the nodes could be, for example, combinations of interconnected electronic devices, such as but not limited to other networks and sub-networks. Also, in the figures the nodes are represented as terminals. However, they could also be workstations, personal computers, printers, scanners, or any other electronic device which can be connected to networks 110.

2. Example Network Connectivity

Figure 5 is a drawing of the connectivity of an example network system. In figure

5, first, third, and fourth nodes **121,123,124** are connected via the network **110** to first, third, and fourth ports **131,133,134** respectively, wherein the first, third, and fourth ports **131,133,134** are located on the first switching device **140**. Also in figure 5, fifth, sixth, and seventh nodes **125,126,127** are connected via the network **110** to fifth, sixth, and seventh ports **135,136,137** respectively and an eighth node **128** is connected via the network **110** to the seventh port **137**, wherein the fifth, sixth, and seventh ports **135,136,137** are located on the second switching device **145**. The first switching device **140** is connected to the second switching device **145** via an eighth port **138** located on the first switching device **140** and via a ninth port **139** located on the second switching device **145** with the eighth port **138** and the ninth port **139** also being connected to the network **110**.

Figure 6 is a drawing of the connectivity of the example network system of figure 5 illustrating the location of typical segments. This figure illustrates the proliferation of segments which can occur when segments are indiscriminately assigned. In figure 6, a first, third, and fourth segments **621,623,624** represent respectively the connectivity of the first, third, and fourth nodes **121,123,124** via the network **110** with the first, third, and fourth ports **131,133,134** on the first switching device **140**. Fifth and sixth segments **625,626** represent respectively the connectivity of the fifth and sixth nodes **125,126** via the network **110** with the fifth and sixth ports **135,136** on the second switching device **145**. In addition, a seventh segment **627** represents the connectivity of seventh and eighth nodes **127,128** via the network **110** with the seventh port **137** on the second switching device **145**. An eighth segment **628** represents the connectivity of the eighth port **138** on the first switching device **140** via the network **110** with the ninth port **139** on the second switching device **145**. Creating topological maps of the network **110** as shown in figure 6 results in a topological segment for every node/switch port pair on the network **110**. In complex networks the proliferation of segments which will change as nodes are added to and removed from the network rapidly becomes unmanageable. Thus, there exists a need for a method of creating a topological map of a network which is accurate, frugal in its utilization of network resources, and which can easily be used to update the network map as changes occur. Considerable simplification in the topological map of figure 6 can

be obtained by replacing the numerous segments in figure 6 with bus, serial, and star segments similar to those of figures 1-4.

Figure 7 is a drawing of a reduced segment topological map 700 of the example network system of figure 5 as described in various representative embodiments of the present patent document. In figure 7, first, third, and fourth segments 621,623,624 of figure 6 are replaced by a first star segment 731; the eighth segment 628 of figure 6 is replaced by a first serial segment 721; fifth and sixth segments 625,626 of figure 6 are replaced by a second star segment 732; and seventh segment 627 of figure 6 is replaced by a first bus segment 711. The bus, serial, and star segments of figure 7 are similar to those of figures 1-4. Once again note the simplification that is obtained. The seven segments of figure 6 have been reduced to four in figure 7. For purposes of clarity in representative embodiments, the various segments of figure 7 would typically be shown interconnected via ports on switches even though the ports on those switches are parts of the segments themselves.

Figure 8 is a flow chart of the method steps performed in creating reduced segment topological maps 700 as described in various representative embodiments of the present patent document.

When there are remaining un-selected switching devices on the network 110, block 810 transfers control to block 820. Otherwise, block 810 terminates the process.

Block 820 selects a previously un-selected switching device and then transfers control to block 830.

When there are remaining un-selected ports on the selected switching device, block 830 transfers control to block 840. Otherwise, block 830 transfers control to block 810.

Block 840 selects a previously un-selected port on the selected switching device and then transfers control to block 850.

Block 850 maps the connection of the electronic device, i.e. the node, connected to the selected port on the selected switching device. Block 850 then transfers control to block 830.

In summary, in representative embodiments reduced segment topological maps

700 are created by combining all switching devices connected to the network with all nodes that are connected to the ports of each switching device. The methods presented may be implemented in a computer program readable by a computer. The computer may be connected to the network.

5 Figure 9A is flow chart of a portion of the method steps of figure 8 performed in creating the reduced segment topological map 700 as described in various representative embodiments of the present patent document. In particular, figure 9A, with related figures 9B and 9C, form an expansion of Block 850 of figure 8. When node has been detected by switching device 140,145 on the network 110, block 905 transfers control to
10 block 910. Otherwise, block 905 transfers control to block 830 of figure 8.

 When other nodes have been detected on the same port by the switching device 140 block 910 transfers control to block 950, otherwise block 910 transfers control to block 915. Block 915 is shown on figure 9B, and block 950 is shown in figure 9C. The connection between blocks 910 and 915 is shown as (A) in figures 9A and 9B, and the
15 connection between blocks 910 and 950 is shown as (B) in figures 9A and 9C.

 Figure 9B is a flow chart of a continuation of a part of the flow chart of figure 9A as described in various representative embodiments of the present patent document. When the detected address belongs to another connector device block 915 transfers control to block 920, otherwise block 915 transfers control to block 935.

20 When serial segment 200 exists on this port of the switching device 140,145, block 920 transfers control to block 930, otherwise block 920 transfers control to block 925.

 Block 925 creates serial segment 200 and then transfers control to block 930.

 Block 930 moves the node to the serial segment 200. Block 930 then transfers
25 control to block 830 of figure 8.

 When a star segment exist on this port of the connector device, block 935 transfers control to block 945, otherwise block 935 transfers control to block 940.

 Block 940 creates star segment 300 and then transfers control to block 945.

 Block 945 moves the node to the star segment 300. Block 945 then transfers
30 control to block 830 of figure 8.

Figure 9C is a flow chart of a continuation of another part of the flow chart of figure 9A as described in various representative embodiments of the present patent document. When bus segment **100** exists on this port of the switching device **140,145**, block **950** transfers control to block **960**, otherwise block **950** transfers control to block **955**.

Block **955** creates bus segment **100**. Block **955** then transfers control to block **960**.

When serial segment **200** exists on this port of the connector device, block **960** transfers control to block **965**, otherwise block **960** transfers control to block **970**.

Block **965** moves the contents of the serial segment **200** to the bus segment **100** and deletes the serial segment **200**. Block **965** then transfers control to block **970**.

Block **970** moves the detected node to the bus segment **100**. Block **970** then transfers control to block **975**.

When the detected node is in existing star segment **300** for the switching device **140,145**, block **975** transfers control to block **980**, otherwise block **975** transfers control to block **830** of figure 8.

When the star segment **300** is empty, block **980** transfers control to block **985**, otherwise block **980** transfers control to block **830** of figure 8.

Block **985** deletes the star segment **300**. Block **985** then transfers control to block **830** of figure 8.

Figure 10 is a drawing of a computer **1000** used for creating and managing reduced segment topological maps **700** for representing the connectivity of nodes **121-127** on the network **110** as described in various representative embodiments of the present patent document. In figure 10, a software program **1020** comprising the method steps of figures 8, 9A, 9B, and 9C is stored on a program storage medium **1010** which could be, for example, a floppy disk, a CD ROM, a hard disk, RAM, or ROM. The memory represented by the program storage medium **1010** could be the main memory of the computer, a cache, or could be maintained remotely. The computer **1000** runs the software program **1020** in order to create and manage the reduced segment topological maps **700**.

3. Concluding Remarks

5 A primary advantage of the embodiment as described in the present patent document over prior techniques is the reduction in the number of segments created in topological maps of the network. The technique of figure 6 creates a total of seven segments for the network of figure 5, while representative embodiments of the present invention create four segments for the same network as shown in figure 7. There is a resultant simplification of the topology of the example network. It is recognized that the topological mapping referred to herein may be contained in one or more tables, and it is not necessarily required for the mapping system to create the map as a drawing. The simplifications provided in the representative embodiments of the present application
10 provide further advantage in reducing the consumption of valuable system resources.

While the present invention has been described in detail in relation to preferred embodiments thereof, the described embodiments have been presented by way of example and not by way of limitation. It will be understood by those skilled in the art
15 that various changes may be made in the form and details of the described embodiments resulting in equivalent embodiments that remain within the scope of the appended claims.

00526830 0231600
009720 02332560